

Atoc Inc. / Topper Rack Products

BT-HT51

"High Topper™"

PARTS LIST

- | | | |
|-------------------------------|-------------------------------|-------------------------|
| (1) High Topper fork mount | (1) Velcro™ wheel strap | (3) long carriage bolts |
| (1) 9 mm quick release skewer | (1) wheel strap retainer clip | (1) short carriage bolt |
| (1) wheel tray | (3) mounting clamps | (4) washers |
| | | (4) nylock nuts |


THINGS YOU WILL NEED to install your High Topper

- ½" wrench
- tape measure
- Thule or Yakima compatible base rack (load bars and towers) for your vehicle

INSTALLATION

The following assumes your High Topper will face forward on your car. You may also position it facing the rear.

1. Check to be sure you have at least 20 inches between the load bars of your base rack for a safe installation. Use the tape measure to measure the center-to-center distance between your load bars and adjust if necessary per your base rack manufacturer's directions.
2. Using two mounting clamps, long bolts, washers, and nuts attach the fork mount to the front load bar. Use the two holes to the sides of the fork mount's riser. See figure below. Do not fully tighten clamps at this time. If you have a severely curved roof and Thule load bars it may be easier to attach the wheel tray if you position the fork mount clamps so that the bolts are behind the load bar, otherwise we recommend positioning the clamps so that the bolts are in front of the load bar.
3. Attach the wheel tray to the rear load bar by placing the remaining mounting clamp around the load bar, slide the head of the remaining long carriage bolt into the slot on the bottom of the wheel tray, and loosely attach it to the mounting clamp with a washer and nut.
4. Connect the wheel tray to the fork mount by sliding the head of the short carriage bolt into the wheel tray slot at the front end of the tray. Pass the short carriage bolt thru the center hole in the base of the fork mount, then attaching the remaining washer and nut.
5. Fully tighten all nuts starting with the one connecting the wheel tray to the fork mount. The mounting clamps are fully tight when the tab between the jaw faces touches the opposite jaw, plus ¼ turn of the nut.
6. Install the WheelCrow wheel strap by placing the wire retainer through the loop in the end of the strap, then sliding the retainer into the slot on the bottom of the wheel tray. NOTE: If your load bars are far apart you may need to position the wheel strap in front of the wheel tray's mounting clamp.
7. Install the skewer into the fork mount.
8. Enjoy riding your bicycle!



If you have any questions please contact your local Atoc dealer or call Atoc at the phone number below.

OPERATION

- 1) Remove all loose objects (such as pumps and water bottles) and recumbent bicycle seats, panniers, or other items that would create excessive wind loading.
- 2) Make sure that the skewer is in the open position and unwrap the wheel strap.
- 3) Remove and stow the front wheel.
- 4) Insert your bicycle's front fork onto the skewer assembly and the rear wheel in the wheel tray.
- 5) Tighten adjuster nut (opposite end of skewer from quick release lever) until firm hand pressure to is required to close the skewer. Do not tighten the skewer by using the quick release lever as a wing nut.

CAUTION: Failure to use the skewer properly can result in the loss of your bicycle. A properly adjusted skewer requires firm hand pressure to close. A rule of thumb is to close the skewer with the palm or heel of your hand. The skewer should leave a distinct impression on your hand. Do not tighten the skewer by using the lever as a wing nut. If there is any question as to the proper use of the skewer, please consult your Atoc dealer.

- 5) Secure the rear wheel by wrapping the WheelCrow wheel strap around the wheel tray and rear wheel.

NOTE: Wrap the WheelCrow wheel strap around the Bike Topper when not in use to keep it from sliding out of the wheel tray slot and becoming lost.

CAUTION:

- Do not attempt to transport bicycles with disk wheels.
- Do not transport bicycles with baby seats, panniers, wheel covers, or full bike covers.
- Atoc strongly recommends that you remove all loose objects such as water bottles, tire pumps, bags, etc. from your bicycle before transporting it.

LIMITED WARRANTY

ATOC, Inc. (ATOC) warrants for one year from purchase date and only to the original retail buyer (Buyer) that ATOC's products are free from defects in materials and workmanship. If Buyer discovers a covered defect, Buyer shall deliver the product to an authorized ATOC dealer with proof of purchase. ATOC will then issue an authorization to the dealer for the return of the product. If there is not a local ATOC dealer or the Buyer purchased the product directly from ATOC, then the Buyer may request to return the defective product directly to ATOC by first contacting ATOC at the address or telephone number set forth below (together with proof of purchase) for authorization. Unauthorized returns will not be accepted. Buyer is responsible for the cost of shipping the product to ATOC.

Upon ATOC's examination and satisfaction of the defect, it will, at its option, repair or replace a defective product free of charge. This is the full extent of ATOC's liability under this Warranty and, upon expiration of the above time periods, all such warranties shall terminate.

Product Warranty Exclusions: No warranty is given for normal wear and tear, unauthorized modifications or alterations, improper installation or maintenance, misuse, negligence, damage, or if its products are used for a purpose for which they were not intended. Specifically, no warranty is given for defects caused by (i) accidents, unlawful vehicle operation, or defects/inconsistencies in the vehicle upon which the product is installed; and (ii) the user's failure to properly secure cargo as recommended by ATOC. This Warranty gives Buyer specific legal rights, and Buyer may also have other rights that may vary from state to state. **EXCEPT AS EXPRESSLY STATED IN THIS WARRANTY, ATOC SHALL NOT BE LIABLE FOR DIRECT, INDIRECT, INCIDENTAL, OR OTHER TYPES OF DAMAGES ARISING OUT OF, OR RESULTING FROM THE USE OF ITS PRODUCT. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE** (Some states do not allow the exclusion or limitation of incidental or consequential damages or allow limitations on the duration of an implied warranty, so the above exclusions may not apply to Buyer).

Atoc Inc. / Topper Rack Products
3615 132nd St SW, Ste C
Lynnwood, WA 98087
(425) 745-2131
www.Atoc.com

Copyright © 2010 Atoc Inc. All rights reserved.